

MATERIAL SAFETY DATA SHEET

SPOTCHECK ® PENETRANT SKL-SP2

IDENTIFICATION

COMPANY ITW INDIA PRIVATE LIMITED

ADDRESS PLOT NO 51, 52,207 & 208, PHASE - 2, IDA

TSIIC, PASHAMMYLARAM,

SANGAREDDY - 502 307, TELANGANA

INDIA.

TELEPHONE 91 - 8455 - 22471091 - 8455 - 224709 FAX PRODUCT USE Visible inspection penetrant

PACKAGES Aerosol,1 L,5 L & 200 L Health 1, Flammability 1(Aerosol Flammability 4), Reactivity 0. NFPA Rating

Revision Date April 1, 2020.

HAZARDOUS INGREDIENTS

Ingredient	Wt/Wt%	CAS#	<u>TLV</u>	PEL	LD 50	LC 50
White mineral oil (petroleum)	60 -80	8042-47-5	5mg/m3	5mg/m3	NA	NA
Phthalic esters	5 - 25		NA	NA	NA	NA
Isobutane (propellant):	30%	75 - 28-5	NA	1000 ppm	NA	NA

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Bland, oily liquid which may irritate the skin and eyes. Bulk material is difficult to ignite, but will burn vigorously if engulfed in fire. Aerosol is extremely flammable

POTENTIAL HEALTH EFFECTS

Skin Contact Can irritate by removing natural skin oils on long or repeated exposures

Eyes May Irritate

Inhalation Not significant at room temperatures. When heated or sprayed, vapors may cause dizziness or nausea

Not significant in small(mouthful)quantities Ingestion

Medical conditions known to be aggravated by exposure to product: None

FIRST AID

Skin Contact : Wash off with soap water .Use soothing lotion

Rinse carefully under upper and lower eyelids using plenty of water Eves

Remove to fresh air if dizzy or nauseated Inhalation

Do not induce vomiting. Accidental ingestion of a small mouthful quantity is not expected to cause significant harm Ingestion

NOTE: In all severe cases, contact physician immediately.

FIRE HAZARD

Conditions of flammability : Aerosol : Spraying near an ignition source will ignite spray mist

Bulk: None unless heated over 93 deg C near ignition source

Min 93 deg C (PMCC) Flash point

Flammable limits in air 1 to 6%

Extinguishing media Carbon dioxide, Foam

Keep containers cool with water spray. Donot spray water directly on burning SKL-SP2. It Special fire fighting procedures

may float and spread the fire

Hazardous combustion products Smoke, soot, oxides or carbon and nitrogen

Unusual fire hazards : Aerosol containers may burst at temperatures over 54 deg C and spray contents into a fire

ACCIDENTAL RELEASE MEASURES

Mop up or Sweep up with absorbent (For disposal see Section 13)

MSDS/SKL SP2/03 dated 04/2020 Page 1 of 2

ISO 9001 ISO 14001 **OHSAS 18001**

ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Sangareddy Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail: magnafluxinfo@magnafluxindia.com, Website: www.in. magnaflux.com



7. HANDLING AND STORAGE

Store away from heat source. Avoid eye contact. Avoid repeated or prolonged skin contact. Avoid breathing spray mist.Donot spray around arcs or flames

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls : None,unless sprayed. Use where ventilation will carry spray mist away from occupied areas
Personal protection : Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable.

Respirator with filter if sprayed in enclosed unventilated space.

9. PHYSICAL PROPERTIES

Initial boiling point (bulk) : Min 235 deg C Vapor pressure : Aerosol 60 psi, Bulk <0.1 mm @ 24 deg C

Percent volatile : None (30% in aerosol) Vapor density : Heavier than air Density/sp. gravity : 0.89 Evaporation rate : Negligible

Water solubility : 0 (emulsifies into water) Appearance : Dark Red oily liquid pH : Odor : Mild oily odour

10. STABILITY AND REACTIVITY

Stability : Stable Incompatibility : None

Hazardous decomposition products : Soot, oxides of carbon and nitrogen when burning

Reactivity : None

11. TOXICOLOGICAL INFORMATION

Carcinogenicity : Contains no known or suspected carcinogens listed with OSHA, IARC, NTP or ACGIH

Threshold limit value : 5mg/cubic meter for oily mist

WHMIS information (Canada) : According to available information, the ingredients have not been found to show reproductive toxicity,

Teratogenicity, Mutagenicity, Skin sensitization, or Synergistic toxic effects with other material.

12. ECOLOGICAL INFORMATION

No data is available on SKL-SP2. It floats on water and can be skimmed off. Its low bulk vapor pressure may exempt it from VOC restrictions. The hydrocarbon propellant is not an ozone depleter.

13. DISPOSAL

As a non-hazardous oily waste, incinerate or send to waste handler who can blend it into secondary fuels. Empty aerosol cans before disposal. Non hazardous waste as per classification in The Hazardous Wastes (Management and Handling) Rules 1989, of CPCB,India

RCRA: Not a hazardous waste U.S EPA Waste number: None

14. TRANSPORTATION

		Bulk (IATA & IMDG)	Aerosol(IATA)	Aerosol(IMDG)
Proper shipping name	:	None, not restricted	Consumer commodity	Aerosols
Hazard class or division	:	None	2.1	2.1
Identification No.	:	None	UN 1950	UN 1950
Packing Group	:	None	-	-

15. REGULATORY INFORMATION

TSCA : All ingredients are listed in TSCA inventory.

CERCLA : Not reportable

SARA TITLE III, Section 313 : No reportable ingredients
California Proposition 65 : Contains nothing on this list

16. OTHER INFORMATION

Revision Statement : Updated the address

MSDS/SKL SP2/03 dated 04/2020 Page 2 of 2



ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Sangareddy Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail: magnafluxinfo@magnafluxindia.com, Website: www.in. magnaflux.com