

MATERIAL SAFETY DATA SHEET

SPOTCHECK [®] PENETRANT SKL-WP2

IDENTIFICATION 1.

COMPANY ADDRESS	:	ITW INDIA PRIVATE LIMITED PLOT NO 51, 52,207 & 208, PHASE – 2, IDA TSIIC, PASHAMMYLARAM, SANGAREDDY – 502 307, TELANGANA INDIA.
TELEPHONE FAX PRODUCT USE PACKAGES NFPA Rating <i>Revision Date</i>		91 – 8455 – 224710 91 – 8455 – 224709 Visible inspection penetrant Aerosol,1 L,5 L & 200 L Health 1, Flammability 1(Aerosol Flammability 4), Reactivity 0. April 1,2020.

HAZARDOUS INGREDIENTS 2

Ingredient	Wt/wt%	CAS#	TLV	PEL	LD 50	LC50
White mineral oil (petroleum)	60-100	8042-47-5	NA	NA	NA	NA
Alcohols (C12-C18),ethoxylated , propoxylated	10-30	69227-21-0	NA	NA	2.6 g/kg (oral/rat)	NA
Alcohols (C11-C15), secondary, ethoxylated	5-10	84133-50-6	NA	NA	2.4 g/kg (oral/rat)	NA
Refined Soyabean oil	5-10	8001-22-7	NA	NA	17.4 g/kg (oral/rat)	NA
9-octadecenamide,N-(2-hydroxy propyl)-(Z)	1-5	111-05-7	NA	NA	NA	NA
Isobutane(propellant – aerosol only)	30	75-28-5	NA	1000 ppm	NA	NA

HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW

Bland, oily liquid which may irritate the skin and eyes. Bulk material is difficult to ignite, but will burn vigorously if engulfed in fire. Aerosol is extremely flammable

POTENTIAL HEALTH EFFECTS

Skin Contac	: Can irritate by removing natural skin oils on long or repeated exposures	
Eyes	: Irritating.	
Inhalation	: Not significant at room temperatures. When heated or sprayed, vapors may cause dizziness or nausea	
Ingestion	: Not significant in small(mouthful)quantities	
1 / l' l	and the sum of the summer of all has a sum a sum of a sum data to Name	

Medical conditions known to be aggravated by exposure to product: None

FIRST AID 4.

Skin Contact : Wash off with soap water .Use soothing lotion Eyes Rinse carefully under upper and lower eyelids using plenty of water Remove to fresh air if dizzy or nauseated Inhalation • Ingestion : Do not induce vomiting

NOTE: In all severe cases, contact physician immediately.

FIRE HAZARD 5

ISO 9001

ΪÅ

Conditions of flammability	: Aerosol : Spraying near an ignition source will ignite spray mist
	Bulk : None unless heated over 93 deg C near ignition source
Flash point	: Min 93 deg C (PMCC)
Flammable limits in air	: 1 to 6%
Extinguishing media	: Carbon dioxide , Foam
Special fire fighting procedures	 Keep containers cool with water spray.Donot spray water directly on burning SKL-WP2.It may float and spread the fire
Hazardous combustion products	: Smoke,soot,oxides or carbon and nitrogen
Unusual fire hazards	: Aerosol containers may burst at temperatures over 54 deg C and spray contents into a fire

MSDS/SKL WP2/03 dated 04/2020

Page 1 of 3

ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Sangareddy Dist.-502307, Telangana State, India ISO 14001 Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail : magnafluxinfo@magnafluxindia.com, Website: www.in. magnaflux.com **OHSAS 18001**

> Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector - 14, Gurgaon - 122 001, Haryana, India. Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com



6. ACCIDENTAL RELEASE MEASURES

Mop up or Sweep up with absorbent (For disposal see Section 13)

7. HANDLING AND STORAGE

Store away from heat source. Avoid eye contact. Avoid repeated or prolonged skin contact. Avoid breathing spray mist.Donot spray around arcs or flames

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls	:	None,unless sprayed. Use where ventilation will carry spray mist away from occupied areas
Personal protection	:	Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable.
		Respirator with filter if sprayed in enclosed unventilated space.

9. PHYSICAL PROPERTIES

Initial boiling point (bulk)	:	Min 235 deg C	Vapor pressure	:	Aerosol 60 psi, Bulk <0.1 mm @ 21 deg C
Percent volatile	:	None (30% in aerosol)	Vapor density	:	Heavier than air
Density/sp. gravity	:	0.88	Evaporation rate	:	Negligible
Water solubility	:	0 (emulsifies into water)	Appearance	:	Red / Violet oily liquid
pH	:	Neutral	Odor	:	Mild odour

10. STABILITY AND REACTIVITY

Stability	:	Stable
Incompatibility	:	None
Hazardous decomposition products	:	Soot, oxides of carbon and nitrogen when burning
Reactivity	:	None

11. TOXICOLOGICAL INFORMATION

Carcinogenicity	:	Contains no known or suspected carcinogens listed with OSHA, IARC, NTP or ACGIH
Threshold limit value	:	5mg/cubic meter for oily mist
WHMIS information (Canada)	:	According to available information, the ingredients have not been found to show reproductive toxicity,
		Teratogenicity, Mutagenicity, Skin sensitization, or Synergistic toxic effects with other material.

12. ECOLOGICAL INFORMATION

No data is available on SKL-WP2. It emulsifies into water and is bio degradable. Its low bulk vapor pressure may exempt it from VOC restrictions. The hydrocarbon propellant is not an ozone depleter.

13. DISPOSAL

As a non-hazardous oily waste, incinerate or send to waste handler who can blend it into secondary fuels. Empty aerosol cans before disposal.

14. TRANSPORTATION U.S.DOT: 49 CFR 172.10	1 Hazardo	ous Material Table	
		<u>Non-aerosol</u>	<u>Aerosol</u>
Proper shipping name	:	None, not restricted	Consumer commodity
Hazard class or division	:	None	ORM-D
Identification No.	:	None	None
Packing Group	:	None	None
IATA : List of Dangerous	Goods		
		<u>Non-aerosol</u>	<u>Aerosol</u>
Proper shipping name	:	None, not restricted	Aerosols,flammable
Hazard class or division	:	None	2.1
Identification No.	:	None	UN 1950
Packing Group	:	None	-
IMDG : General Index			
		<u>Non-aerosol</u>	<u>Aerosol</u>
Proper shipping name	:	None, not restricted	Aerosols
Hazard class or division	:	None	2.1
Identification No.	:	None	UN 1950
Packing Group	:	None	-

MSDS/SKL WP2/03 dated 04/2020

Page 2 of 3



ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Sangareddy Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail : magnafluxinfo@magnafluxindia.com, Website: www.in. magnaflux.com

> Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector - 14, Gurgaon - 122 001, Haryana, India. Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com Corporate Identity Number (CIN) : U32301HR1979PTC038643



15. REGULATORY INFORMATION

TSCA CERCLA SARA TITLE III, Section 313 California Proposition 65 WHMIS Class (Canada) All ingredients are listed in TSCA inventory. Not reportable No reportable ingredients Contains nothing on this list Non-Aerosol : D2-B Aerosol : A,B-5,D2-B

Note ; This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

16. OTHER INFORMATION

Revision Statement : Updated the address

ċ

.

:

:

MSDS/SKL WP2/03 dated 04/2020

Page 3 of 3



ITW India Private Limited, Plot no:51, 52, 207 & 208, Phase -2, IDA, TSIIC, Pashammylaram, Sangareddy Dist.-502307, Telangana State, India Telephone: +91 8455 224710. Facsimile: +91 8455 224709. E-mail : magnafluxinfo@magnafluxindia.com, Website: www.in. magnaflux.com

> Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector - 14, Gurgaon - 122 001, Haryana, India. Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com